



KONICA MINOLTA

TECHNOLOGY



AccurioPrint C3070L

COLOR DIGITAL PRODUCTION PRESS / COPIER / SCANNER

- 70 ppm output for mid-volume color print production
- Simitri® HDE toner with biomass to protect the environment
- SEAD V screen-enhancing active digital processing system
- Real-time image density adjustments
- 4,250-sheet paper capacity, auto duplex up to 300 gsm

- Print both banners and envelopes from a single system
- 80-page booklet-making, 2/3-hole punch, post-insertion options
- Choice of exclusive Konica Minolta or Fiery® image controller
- High-speed dual scanning at 240 ipm
- Compact design with rugged, long-lasting durability

AccurioPrint C3070L

COLOR DIGITAL PRODUCTION PRESS / COPIER / SCANNER

AccurioPrint series brings it all: 70 ppm print/copy output, advanced processing for resolution equivalent to 3,600 dpi, our exclusive Simitri HDE toner for offset-quality color at an affordable cost, superior stability over long print runs on a variety of substrates — and inline finishing options to handle a broad array of job specs.

SYSTEM SPECIFICATIONS

ACCURIOPRINT C3070L

Resolution	1,200 x 1,200 dpi (3,600 equivalent) 8-bit, 256 gradations
Paper weight	Standard: 62–256 gsm Opt.: MB-506 – 350 gsm, LU-202XL/m – 300 gsm
Duplex unit	62–350 gsm
Paper sizes (max.)	Standard: 330 x 487 mm (13" x 19.2") Opt.: MB-506 – 330 x 1200 mm LU-202XL – 330 x 750 mm
Image loss (max.)	4 mm or less for top edge 4.5 mm or less for bottom edge 3.0 mm or less for right/left edges
Paper input capacity	Standard: 1,500 sheets Max.: 4,250 sheets
Paper output capacity	Max.: FS-531 Finisher – 3,000
Main unit dimensions (W x D x H)	31.5" x 35.6" x 42.4"
Main unit weight	703 lb
Power requirements	AC208 – 240 V, 60 Hz, 24A dedicated line

PRODUCTIVITY

8.5" x 11" (max. per minute)	70 ppm
Monthly duty cycle	758,000 pages

CONTROLLER

IC-605A/B Internal	IC-605A
Konica Minolta controller	
IC-417 Internal EFI controller	Available

SCANNER SPECIFICATIONS

Scan speed (8.5" x 11")	120 ipm simplex / 240 duplex
Scan resolution	600 x 600 dpi
Scan modes	TWAIN scan, Scan-to-HDD, Scan-to-FTP, Scan-to-SMB, Scan-to-Email, Scan-to-USB
Scan formats	PDF, TIFF, JPEG (all controllers), Secured PDF, Compact PDF, XPS, PDF/A-1a, 1b (with IC-605)

COPIER SPECIFICATIONS

Gradations	256 gradations
First copy out	6.5 sec. or less
Magnification	25–400%, in 0.1% steps

KONICA MINOLTA IMAGE CONTROLLER IC-605

Type	Embedded
CPU	Intel Core i5 4570S 2.9 GHz
Memory	Max.: C3070 – 18 GB including UK-104, C3070L – 14 GB (UK-104 not compatible)
HDD	Max.: C3070 – 3.5 TB including UK-104, C3070L – 3 TB (UK-104 not compatible)
Page-description language	PS3 (CPSI3020), PDF version 1.7, TIFF version 6 compliant, PPML version 2.2, PCL5c compatible, PCL XL (PCL6 version 3) compatible, APPE version 4.2*1, PDF/VT version 2*1
Printing method	TCP/IP, NetBEUI, IPP, WSD, SMB, Bonjour
Applicable OS	Windows Server 2008*1/R2, 7, 8.1 Server 2012/R2, 10, Server 2016 Mac OS X v10.8 – v10.12
Interface	Ethernet (1000BASE-T / 100Base-TX / 10Base-T)

*1UK-104 + UK-218 required, not compatible with C3070L.

FIERY IMAGE CONTROLLER IC-417

Type	Embedded
CPU	Intel® Celeron® Processor G1820 (2M Cache, 2.70 GHz)
Memory	2 GB
HDD	500 GB SATA
Page-description language	Adobe PostScript3 (PS3020), PDF 1.7, PCL 5/6 emulation
Printing method	TCP/IP, SNMP, SMB, FTP, LPR, IPP, Bonjour
Applicable OS	Windows 7 / 8.1 / 10*1 Windows Server 2008 / 2012*1 Mac OS X v10.8 / v10.9 / v10.10

*1Including 64-bit versions.

OPTIONS

DF-706	Automatic document feeder
EF-103	Envelope fusing
FS-531	50-sheet staple finisher
FS-612	Booklet finisher
HT-503	Dehumidification heating unit for LU-202
LU-202m	Paper feed tray
LU-202XL	Extra long paper feed unit (29.5" max.)
LU-202XLm	Extra long paper feed unit (29.5" max.)
MB-506	Multi-bypass tray
MK-732	Mount kit for PI-502
MK-740	Media feeding kit for banner printing (300 sheets)
MK-740m	Media feeding kit for banner printing (1,000 sheets)
MK-746	Envelope Print Guide for LU-202m and LU-202XL
OC-511	Original cover
OT-510	Open stacker (3,000-sheet stacking)
OT-511	Output tray
PI-502	Multi-post inserter
PK-512	2/3-hole punch kit for FS-612/FS-531
WT-511	Working table

See brochure for full product options available.

For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2018 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA and the KONICA MINOLTA logo are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.
100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item #: APC3070LSS
8/2018-C